



Compact Laminator SF-390E

Description

The Compact Laminator is an entry-level laminator that provides good quality double-sided lamination for roll film encapsulation, an affordable and efficient solution for your business.

The device has an elongated manual feed conveyor with the possibility of longitudinal cutting and perforation, which greatly simplifies the work of the operator.

The roll laminators feature a unique anti-curl technology synchronized with the control panel, which ensures that whatever you are laminating - a menu, a book cover, or a sheet of business cards - comes out flat, with no curl or blister.

The main features of the Compact Laminator SF-390E model:

- Manual feed
- Bilateral lamination
- Temperature control separately
- Pressure shafts electrically controlled
- Compact design
- Anti-twist function
- Bottom roller with non-stick coating
- Steel roller for uniform heating
- Device for longitudinal cutting and perforation

Specifications

Lamination width	375 mm
Sleeve diameter	25 / 77 mm
Temperature	80-140°C
Lamination thickness	0.5mm
Heating system	steel roller
Lamination	hotter
Frame	Metal
Power supply	220 V
Weight	65 kg
Power	1600 W
Depth	680 mm
Length	1250 mm
Height	450 mm
Speed	6 m/min
Paper density	400 g/sq.m
Liner winder	No
Perforation	Yes
Temperature control	Yes
Speed control	Yes
Liquid crystal display	Yes