

SF-540A

Auto Laminator



Product Introduction

Automatic laminator- Heavy duty from **DFS** is a hot laminator that allows the flexibility of single side OPP roll film lamination and encapsulation providing an affordable and effective solution to outsourcing.

It is built for continuous use on an everyday basis, and constructed using parts of the highest quality only. The hydraulic laminator has been designed to help breathe life into your business by allowing you provide customers with a service you previously had to outsource, enabling you to offer your customers a true one-stop shop.

The automatic laminator was designed to help breathe life into your business by allowing you to provide your customers with a service you previously had to outsource. It has anti-curl technology to ensure that whatever you laminate comes out smooth and flat. Also it has an automatic feed with auto-overlap. This is the best value single-sided laminator on the market, is simple to use, easy to maintain, quick and reliable.

The automatic feed with auto-overlap makes it easy to feed your work through the laminator and the separator ensures it's ready for the guillotine the moment it's been laminated.

Automatic laminators from **DFS** have unique anti-curl technology, in sync with the control panel, ensures that whatever you laminate – a menu, a book cover or a sheet of business cards – comes out flat with no curl or uplift.

Email: info@digital-finishing-systems.com Website: digital-finishing-systems.com



SF-540A

SF-540A

Auto Laminator

Main Feature

- Auto feeding with air suction
- Pneumatic auto separation
- Heavy duty construction
- 20m/min laminating speed
- Mirror chrome heating roller
- Thermal or Cold laminating
- Touch screen display system
- Digital foiling
- Adjustable electric hydraulic pressure system
- Large feeding volume, 2500 sheets, 200gsm paper

Application



Technical Parameters

| Model | SF-540A |
|---------------------|----------------------------|
| Roll film width | 540*760mm |
| Roll film thickness | 17-45 mic |
| Speed | 20m/min |
| Feeding mode | Dual air suction |
| Core | 3 inch |
| Auto feeding | Yes |
| Voltage | 380V, three phase, 50-60Hz |
| Weight | 510kg(G.W.) |
| Laminating material | BOPP film |
| Paper thickness | 130-450 g/m ² |
| Temperature | 20-140°C |
| Pressure control | Hydraulic |
| Display | 7 inch touch screen |
| Foil feature | Yes |
| Power | 6.5kw(total) |
| Size(mm) | 1500*1150*1350(Machine) |